

紡織實驗室

Test Report 報告號碼: TX52039 /2024 /SH 日期: 2024 年 05 月 27 日頁數: 三 之 一 頁

新光紡織股份有限公司

臺北市中山區中山北路 2 段 44 號 15 樓

我們依照客戶的要求, 根據申請者送交的樣品進行測試如下:

樣品敘述 : 一塊梭織布 PP-P2485-4(新式運動短褲)

顏色 : 丈青色

成份 : 100% Recycled Polyester

布重 : 104gsm

軍方規格品名 : 新式運動短褲

軍方規格編號 : CMS-N-000308A

申請者 : 新光紡織股份有限公司

收件日期 : 2024 年 05 月 20 日

測試週期 : 2024 年 05 月 20 日至 2024 年 05 月 24 日

測試項目&測試方法 : 依申請者要求進行下列測試

測試結果 : 請參照下一頁結果

- 測試樣退還給申請者 -

台灣檢驗科技股份有限公司

張家豪

張家豪
技術經理



"Unless otherwise stated the results shown in this test report refer only to the sample(s) tested, and such sample(s) are retained for 1 months only." This test report cannot be reproduced, except in full, without prior written permission of the Company.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law."

紡織實驗室

Test Report 報告號碼: TX52039 /2024 /SH 日期: 2024 年 05 月 27 日 頁數: 三 之 二 頁

測試結果:

1. 纖維成份分析 (依美國紡織化學協會 AATCC 20:2021)

聚酯纖維	100%
------	------

2. 經緯紗密度 (依美國材料試驗協會 ASTM D3775-14)

經紗根數/2.54 公分	135.0
緯紗根數/2.54 公分	81.0

3. 單位面積之質量 [依美國材料試驗協會 ASTM D3776/D3776M-20 Option C]

公克/每平方公尺	107.7
----------	-------

4. 抗拉強力 (依美國材料試驗協會 ASTM D5034-21 - Grab method, CRE)

經向	95.4 lbs*
緯向	138.1 lbs*

*測試樣品於接近夾頭處破裂

5. 撕裂強度 (依美國材料試驗協會 ASTM D1424 - 21 - Elmendorf condition 1 without wetting)

橫跨經向	3.4 lbs
橫跨緯向	4.0 lbs

6. 吸水性 (依美國紡織化學協會 AATCC 79 - 2018 - 滴下法)

正面	2.0 秒
----	-------

"Unless otherwise stated the results shown in this test report refer only to the sample(s) tested, and such sample(s) are retained for 1 months only." This test report cannot be reproduced, except in full, without prior written permission of the Company.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law."

紡織實驗室

Test Report 報告號碼: TX52039 /2024 /SH 日期: 2024 年 05 月 27 日頁數: 三 之 三 頁

測試結果:

7. 垂直吸濕 (依日本工業規格協會 JIS 1907:2010 Section 7.1.2 Byreck 法)

10 分鐘後	
經向 (mm)	124
緯向 (mm)	133

8. 耐摩擦染色堅牢度 (依美國紡織化學協會 AATCC 8 - 2016e(2022)e)

乾式	4.5 級
濕式	4.5 級

備註: 級數依據 5 階灰色標評定, 1 為最差, 5 為最好

9. 耐水洗染色堅牢度 (依美國紡織化學協會 AATCC 61:2013e(2020) 2A at 120°F)

變褪色	4.5 級
對醋酸纖維污染度	4.5 級
對棉纖維污染度	4 級
對尼龍纖維污染度	3.5 級
對聚酯纖維污染度	4.5 級
對亞克力纖維污染度	4.5 級
對羊毛纖維污染度	4.5 級

備註: 級數依據 5 階灰色標評定, 1 為最差, 5 為最好

10. 汗液染色堅牢度 (依美國紡織化學協會 AATCC 15:2021)

變褪色	4.5 級
對醋酸纖維污染度	4.5 級
對棉纖維污染度	4.5 級
對尼龍纖維污染度	4.5 級
對聚酯纖維污染度	4.5 級
對亞克力纖維污染度	4.5 級
對羊毛纖維污染度	4.5 級

備註: 級數依據 5 階灰色標評定, 1 為最差, 5 為最好

*** 結 束 ***

"Unless otherwise stated the results shown in this test report refer only to the sample(s) tested, and such sample(s) are retained for 1 months only." This test report cannot be reproduced, except in full, without prior written permission of the Company.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law."